


AHPT-1304HTG+HV / Planetary Full HV Servo+HS+TG

(Ultra High Speed)

Control System	Positive PWM control 1500 usec Neutral	
Operating Voltage Range	6.0V ~ 8.4V	
Operating Temperature Range	-20C° ~ +90C° (-4°F ~ 194°F)	
Test Voltage:	Stall Torque	Motion Speed
At 6.0V	8.8 kg/cm , 120 oz/in	0.08 sec / 60 deg at no load
At 7.4V	10.2 kg/cm , 131 oz/in	0.06 sec / 60 deg at no load
At 8.4V	13.1 kg/cm , 176 oz/in	0.04 sec / 60 deg at no load
Idle Current	2mA at stopped	2mA at stopped
Running Current	330mA at no load	345mA at no load
Stall Current	920mA	1050mA
Dead band width	2 usec	2 usec
Operation Travel	45°/ one side pulse travel 400 usec	
Direction	Re-clock wise/ Pulse Travel 1500 to 2000 usec	
Motor Type	Japan Brushless motor	
Potentiometer Type	4 Slider/indirect drive	
Amplifier Type	6A Treble Power MOS-FET	
Dimensions	41 x 21.0 x 35.7 mm / 1.61 x 0.82 x 1.11 inch.	
Weight:	68grams / 1.87oz without splined horn	
Ball Bearing	Dual / M10x6	
Gear Material	Planetary Stainless Gears	
Waterproof	IP47 Rating Rank	
Horn Gear Spline	Metal 25 Tooth (External diameter: 5.9mm)	
Connector Wire Length	300mm (9.85inch)	
Connector Wire Stand Counter	60EA	
Connector Wire Gauge	22AWG	
Wire Info (Black)	- Negative	
Wire Info (Red)	+ Positive	
Wire Info (White)	S Single	
Spare Parts Items		
Servo Gear Set	<#10706> AHPT-1304HTG+HV(Metal Gears)	
Servo Case Set	<#10707> AHPT-1304HTG+HV(Outside case)	
Servo Accessories	<#10708> AHPT-1304HTG+HV(Accessories - Horn & screws & rubber)	

Version: 1.1

Update: 2015/2/5